



STACK WASHER-DRYER

FOR SEMI-COMMERCIAL LAUNDRY APPLICATIONS (OPL)

INDUSTRIAL
BY DESIGN

Washer

- Stainless steel inner and outer drum for long-lasting worry free performance
- Four-compartment soap box for wash, pre-wash, bleach and softener
- Dynamic Balancing System
 - » Suspension & out-of-balance logic manages and redistributes unbalanced loads
 - » Quiet operation
- High-speed Extract
 - » A 1200 RPM extract speed delivers 440 G-Force
- Door opens 180° for easy loading and unloading
- Large capacity
- Ultra-low water use of only 11.7 gallons per cycle

Dryer

- Superior Airflow
 - » Fast-drying results with advanced airflow pattern
- Large Capacity
 - » Large 7.0 ct. ft. cylinder
- Time Savings
 - » Large, easy-clean lint filter is located upfront

Control

- Electronic Homestyle Control
 - » Digital display
 - » Six preset cycle options
 - » Customizable cycles
 - » Cycle time countdown
 - » LED progress indicators



STACK WASHER-DRYER

Specifications	Washer	Dryer
Available Controls	Electronic Homestyle	
Capacity - lb (kg)	21.5 (9.5)	18 (8.2)
Cylinder Volume - cu. Ft. (liters)	3.42 (96.8)	7.0 (198)
Width - in (mm)	26 7/8 (683)	
Depth - in (mm)	27 3/4 (704)	
Height - in (mm)	78 3/16 (1986)	
Spin Speed - G-Force (RPM)	440 (1200)	N/A
Motor Size - HP (kw)	Variable Speed Induction 0.9 (0.67)	1/3 (0.25)
Water Consumption per Cycle - g (l)	11.7 (44.3)	N/A
WF (Water Factor)	3.7	N/A
MEF (Modified Energy Factor)	2.38	N/A
Available Heat Sources	N/A	Gas or Electric
Available Heating Element (Electric W)	N/A	4750 @ 208V 5350 @ 240V
Gas Inlet Connection - in (mm)	N/A	3/8 (9.5)
Gas Consumption - BTU/Hr	N/A	22,500
Exhaust Outlet Diameter - in (mm)	N/A	4 (102)
Exhaust Airflow - cfm (liters/sec)	N/A	220 (105)
Available Water Temperatures	3	N/A
Available Cycles	Heavy Duty, Normal Eco, Perm Press, Delicate, Rinse and Spin, Spin Only	Regular, Perm Press, Delicate, Time Dry, Quick Dry, Fluff Up
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)	N/A
Cycle Indicator Lights	Yes	
Cylinder Finish	Stainless Steel	Galvanized
Available Colors	White	
Door Type (Solid/Window)	Window	
Available Electrical Requirements - (Voltage/Hz/Ph)	120/60/1 - 15 Amp	Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp Electric: 120/208/60/1 - 30 Amp
Canada Only Available Electrical Requirements - (Voltage/Hz/Ph)	Gas: 120/60/1 - 20 Amp - 1 Cord Electric: 240/60/1 - 48 Amp - 1 Cord Electric: 208/60/1 - 48 Amp - 1 Cord	
Net Weight - lb (kg)	390 (177)	
Shipping Weight - lb (kg)	425 (193)	
Shipping Dimensions		
Width - in (mm)	29 (737)	
Depth - in (mm)	32 3/4 (832)	
Height - in (mm)	80 (2032)	
Available Agency Approvals	cUL _{US}	Elec: cUL _{US} , Gas: cCSA _{US}

Note: Not all options are available for all models. Refer to the price list for the available models and options.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

Alliance Laundry Systems LLC
Shepard Street
Ripon, WI 54971

©Copyright 2015 Alliance Laundry Systems LLC

